





Filtration Manifold

- < 4 units**
 - N 816.3KT.18
16 l/min
20 mbar
- < 6 units**
 - N 938.50 KT.18
30 l/min
15 mbar
 - N 840G
34 l/min
6 mbar

Solide Phase Extraction Single & Manifold

- 1 unit <500ml**
 - N 96
7 l/min
<130 mbar
- 1 unit >500ml**
 - N 816.3KT.18
16 l/min
20 mbar
 - N 840 G
34 l/min
6 mbar

Degassing

- < 1L flask**
 - N 816.3KT.18
16 l/min
20 mbar
- > 1L flask**
 - N 938.50 KT.18
30 l/min
15 mbar
 - N 820 G
20 l/min
6 mbar

Filtration Devices

- < 1liter**
 - N 96
7 l/min
<130 mbar
- 1 - 3 L**
 - N 816.1.2 KT.18
30 l/min
100 mbar
- 5 L or liquid viscous**
 - N 938.50 KT.18
30 l/min
15 mbar
 - N 840 G
34 l/min
6 mbar

Dessication



- Dessicator <25cm Ø**
 - N 816.3KT.18
16 l/min
20 mbar
- Dessicator >25cm Ø**
 - N 938.50 KT.18
30 l/min
15 mbar
 - N 820G
20 l/min
6 mbar

Manifold



- 2-12 Positions**
 - N 816.3KT.18
16 l/min
20 mbar
 - N 938.50 KT.18
30 l/min
15 mbar
- 12-24 Positions**
 - N 840 G
34 l/min
6 mbar

Aspiration Fluids

- N 96
7 l/min
<130 mbar
- N 816.3KT.18
16 l/min
20 mbar
- N 820 G
20 l/min
6 mbar